

STENCIL PRINTING MACHINE

BACKGROUND OF THE INVENTION

The present invention relates to stencil printing machines for transferring
5 print medium in pressured state between a printing drum, to which a stencil
sheet is mounted, and a press rotary member to press the printing drum to
perform a printing operation and, more particularly, to a stencil printing
machine having two sets of printing drums and press rotary members for
performing a double-face printing operation.

10 FIG. 1 shows a schematic overall structure of a conventional a stencil
printing machine that enables a double-face printing operation. As shown in
FIG. 1, the stencil printing machine 100 is constructed of upstream and
downstream stencil making sections 104, 105 with respective thermal printing
heads 102, 103 for thermally perforating respective stencil sheets 101, 101 on
15 the basis of respective image data, an upstream printing section 109 wherein
the stencil sheet 101 made in the upstream stencil making section 104 is
mounted onto an upstream printing drum 106 and a print sheet 107, which is
fed thereto, is transferred through a path between the upstream printing drum
106 and a press roller 108 in a pressured contact relationship to transfer ink
20 onto an upper surface (one surface) of the print sheet 107 during such a
transfer step, a paper feed section 110 which feeds the print sheet 107 to the
upstream printing section 109, an upstream belt-conveyer transfer unit 111
located at a sheet discharge side of the upstream printing section and
transferring the print sheet 107 to a downstream side with the action of a belt
25 121, a downstream printing section wherein the stencil sheet 101, which is
made in the downstream stencil making section 105, is mounted onto a
downstream printing drum 112 and the print sheet, which is fed from the
upstream belt conveyer transfer unit 111, is transferred through a path
between the printing drum 112 and a press roller 114 in a pressured contact
30 relationship to transfer ink onto a lower surface (the other surface) of the print
sheet 107 during such a transfer step, and a downstream belt-conveyer
transfer unit 117 with a belt 122 located at a sheet discharge side of the
downstream printing section 115 for transferring the print sheet 107 to a sheet

discharge tray 116 located in a downstream side.

Further, the upstream and downstream printing sections 109, 115 include squeegee rollers 123, 123 located inside the printing drums 106, 112, respectively, and held in contact with inner surfaces of outer peripheral walls 106a, 112a of the respective printing drums 106, 112, doctor rollers 124, 124 located in close proximity to the squeegee rollers 123, 123, respectively, to form respective given gaps relative thereto, and ink supply units 125, 125 each for supplying ink to an each area between the rollers 123, 124, with the squeegee rollers 123, 123 being arranged to rotate on inner peripheral surfaces of the outer peripheral walls 106a, 112a in association with rotations of the respective printing drums 106, 112. In addition, as the squeegee rollers 123, 123 rotate with the rotations of the printing drums 106, 112, the outer peripheral surfaces of the squeegee rollers 123, 123 are adhered with ink in a given film thickness, with the adhered ink being transferred to the outer peripheral walls 106a, 112a to allow ink to be supplied to an inner side of the stencil sheet 101 at all times.

Now, the double-face printing operation is described below. Rotations of the printing drums 106, 112 allow the print sheet 107 to be fed from the paper feed section 110 to the upstream printing drum 106 in synchronism with the rotation thereof. The print sheet 107, thus fed to the printing drum 106, is brought into pressured contact with the stencil sheet 101 of the printing drum 106 with the press roller 108 to allow ink image to be transferred onto the upper surface of the print sheet 107, with the print sheet 107, whose upper surface is printed, being peeled off from the outer peripheral wall of the printing drum 106 and being introduced to the upstream conveyer-belt transfer unit 111. The upstream belt-conveyer transfer unit 111 causes the belt 121 to move for transferring the print sheet 107 with its lower surface remaining contact with the belt, thereby feeding the print sheet 107 from the most downstream side of the belt 121 to the downstream printing drum 112. The print sheet 107, thus fed to the downstream printing drum 106, is then brought into pressured contact with the stencil sheet 101 of the printing drum 112 with the press roller 114 to transfer ink image onto the lower surface of the print sheet 107, with the print sheet 107, whose lower surface is printed,

being peeled off from the outer peripheral wall of the printing drum 112 to be introduced to the downstream belt-conveyer transfer unit 117. The downstream belt-conveyer transfer unit 117 causes the belt 122 to move for transferring the print sheet 107 from the most downstream side of the belt 122 to the sheet discharge tray 116. The print sheet 107 thus discharged to the sheet discharge tray 116 is placed therein in the stacked state.

Also, a similar technology related to such a stencil printing machine 100 is disclosed in Japanese Patent Provisional Publication No. 8-90893.

By the way, in the aforementioned stencil printing machine for the double-phase printing operation, the print sheet 107, whose upper surface has been printed with the upstream printing section 109, is fed to the downstream printing section 115 in a non-fixed ink state to cause the press roller 114 of the downstream printing section 115 to press the upper surface, which remains in the non-fixed ink state, of the print sheet 107. Accordingly, as shown in FIG. 2, the outer circumferential periphery of the press roller 114 and non-fixed ink 130 of the print sheet 107 are brought into surface contact in a wide range. For this reason, when the press roller 114 is separated from the print sheet 107, non-fixed ink area 130 remaining at the contact surface is caused to be split such that a portion of non-fixed ink 130 is adhered to the press roller 114. When this takes place, non-fixed ink is transferred to the press roller 114 and is then transferred to the print sheet 107, providing an issue of contamination in the print sheet 107.

To address such an issue, it is thought for providing a means for washing ink transferred to the press roller 114 with a waste.

However, with such a means for washing ink adhered to the press roller 114, a mechanism for washing becomes complicated in structure and, also, a new issues is encountered in that ink is transferred from the print sheet 107 to the press roller 114, resulting in a decrease in the print density of the print sheet 107.

On the other hand, with such a stencil printing machine which enables only a single-phase printing operation, when the print sheet is not fed between the printing drum and the press roller to cause the press roller to be brought into direct contact with the stencil sheet owing to a jamming operation, when

the print sheet whose size is smaller than a lateral size of the stencil sheet and a portion of the press roller is brought into direct contact with the stencil sheet and when the single-phase printing operation is implemented and the other surface of the print sheet in non-fixed ink state is subjected to the printing operation, there are some instances wherein ink is transferred to the press roller and transferred ink is further transferred to the print sheet, with a resultant contamination in the print sheet.

SUMMARY OF THE INVENTION

The present invention has been made to address the aforementioned issue and has an object to provide a stencil printing machine which is able to prevent print medium from being contaminated with little decrease in a print density of print medium with a simplified structure.

An important feature of the invention as defined in claim 1 concerns a stencil printing machine having a printing section composed of a rotary printing drum with an outer circumferential periphery to which a stencil sheet is mounted and a rotary press member which is moveable between a pressurized position to be pressed against the outer circumferential periphery of said printing drum and a separated position to be separated from the outer circumferential periphery of said printing drum, and a paper feed section for feeding print medium between said printing drum and said rotary press member, wherein print medium, fed from the paper feed section, is pressed between and transferred by said printing drum and said rotary press member both of which are rotated together, and during such a pressurized and transfer movement of print medium, print medium is transferred with ink to perform a printing operation, and wherein the stencil printing machine comprises said rotary press member including an outer circumferential periphery formed with micro-convexities and micro-concavities.

With such a stencil printing machine, contamination of print medium is prevented only by providing the micro-convexities and the micro-concavities over the outer circumferential periphery of the rotary press member so that even when the rotary press member is brought into directly pressured contact with the stencil sheet, the rotary press member has a decreased contact surface

area with ink, or the outer circumferential periphery of the rotary press member has a reduced contact surface area with the surface, with non-fixed ink, of print medium and, when the rotary press member is separated from the stencil sheet, or when the rotary press member is separated from print sheet, 5
aforementioned ink or non-fixed ink, which remains at a portion with which the rotary press member is not brought into contact, are not adhered to the rotary press member to interrupt the rotary press member from being appreciably adhered with non-fixed ink.

Another important feature of the invention as defined in claim 2 10
concerns the stencil printing machine wherein said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press member has a depth of a value above 0.035 mm.

With such a stencil printing machine, the effect of the invention defined in claim 1 is obtained and, in addition, when the rotary press member presses 15
the printing drum via print medium, there is a big difference in level in the convexities and the concavities to interrupt the concavities from being practically brought into contact with non-fixed ink of print medium, thereby adequately minimizing transfer of non-fixed ink to the rotary press member.

Another important feature of the invention as defined in claim 3 20
concerns the stencil printing machine wherein said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press member has a depth of a value above 0.044 mm.

With such a stencil printing machine, the effect of the invention defined in claim 1 is obtained and, in addition, when the rotary press member presses 25
the printing drum via print medium, there is an adequately big difference in level in the convexities and the concavities such that the concavities have little or no contact with non-fixed ink of print medium, thereby further minimizing transfer of non-fixed ink to the rotary press member.

Another important feature of the invention as defined in claim 4 30
concerns the stencil printing machine defined in claims 1 to 3 wherein a distance between apexes of said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press member has a value below 0.64 mm.

With such a stencil printing machine, the effects of the invention defined in claims 1 to 3 is obtained and, in addition, when the rotary press member presses the printing drum via print medium, there is a narrow distance between the convexities and the concavities formed over the outer circumferential periphery of the rotary press member, interrupting the print image from appearing a visible convexity and concavity pattern.

Another important feature of the invention as defined in claim 5 concerns the stencil printing machine defined in any one of preceding claims 1 to 4 wherein said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press member are composed of point-like convexities and concavities.

With such a stencil printing machine, the effects of the invention as defined in claims 1 to 4 are obtained and, in addition, the convexities and the concavities can be uniformly formed in either direction over the outer circumferential periphery of the rotary press member.

Another important feature of the invention as defined in claim 6 concerns the stencil printing machine defined in any one of preceding claims 1 to 4 wherein said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press member are composed of line-shaped convexities and concavities which are orientated in the same direction as that which print medium is transferred.

With such a stencil printing machine, the effects of the invention as defined in claims 1 to 4 are obtained and, in addition, the convexities and the concavities can be regularly and distinctly formed over the outer circumferential periphery of the rotary press member in a direction perpendicular an axial direction thereof.

Another important feature of the invention as defined in claim 7 concerns the stencil printing machine defined in claim 5 wherein said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press member are formed by locating a screen mesh to a surface of said rotary press member.

With such a stencil printing machine, the effect of the invention as defined in claim 5 is obtained and, in addition, the screen mesh per se is

individually prepared whereupon the screen mesh is located over the outer circumferential periphery of the rotary press member by covering or by adhering for thereby enabling formation of the micro-convexities and the micro-concavities.

5 Another important feature of the invention as defined in claim 8 concerns the stencil printing machine defined in claim 5 wherein said point-like micro-convexities and micro-concavities of the outer circumferential periphery of said rotary press member are formed by locating a large number of spherical bodies to a surface of said rotary press member.

10 With such a stencil printing machine, the effect of the invention as defined in claim 5 is obtained and, in addition, the large number of spherical bodies per se are individually prepared whereupon the spherical bodies are located over the outer circumferential periphery of the rotary press member by adhesion for thereby enabling formation of the micro-convexities and the micro-concavities.

15 Another important feature of the invention as defined in claim 9 concerns the stencil printing machine, defined in claim 1, which further comprises a liquid application unit for applying liquid to the outer circumferential periphery of said rotary press member.

20 With such a stencil printing machine, the effect of the invention as defined in claim 1 is obtained and, in addition, during separating movement between the rotary press member and print medium, a non-fixed ink area is not split whereas a liquid area is split, thereby preventing non-fixed ink from being adhered to the rotary press member.

25 Another important feature of the invention as defined in claim 10 concerns the stencil printing machine, defined in claim 9, wherein said liquid has a viscosity of a value below 1000 millipascal·second (mPa·s).

30 With such a stencil printing machine, the effect of the invention as defined in claim 9 is obtained and, in addition, during separating movement between the rotary press member and print medium, the liquid area, which has the low viscosity, is reliably split, thereby preventing non-fixed ink from being adhered to the rotary press member.

Another important feature of the invention as defined in claim 11

concerns the stencil printing machine, defined in claim 9, wherein said liquid has a viscosity of a value below 500 millipascal·second (mPa·s).

With such a stencil printing machine, the effect of the invention as defined in claim 9 is obtained and, in addition, during separating movement between the rotary press member and print medium, the liquid area, which has the lower viscosity, is more reliably split, thereby preventing non-fixed ink from being adhered to the rotary press member.

Another important feature of the invention as defined in claim 12 concerns the stencil printing machine, defined in claims 9 to 11, wherein said liquid is composed of silicone oil.

With such a stencil printing machine, the effects of the invention as defined in claim 9 to 11 are obtained with the use of silicone oil.

Another important feature of the invention as defined in claim 13 concerns the stencil printing machine, defined in claim 9, wherein said liquid application unit comprises a rotary liquid application roller held in pressured contact with said rotary press member, and a liquid supply unit for supplying liquid to an outer circumferential periphery of said liquid application roller, wherein said liquid application roller is rotatable with said rotary press member to apply liquid, supplied by said liquid supply unit, to the outer circumferential periphery of said rotary press member.

With such a stencil printing machine, the effect of the invention as defined in claim 9 is obtained and, in addition, the liquid application roller rotates with the rotary press member to apply liquid to the rotary press member.

Another important feature of the invention as defined in claim 14 concerns the stencil printing machine, defined in claim 9, wherein said liquid application unit comprises a sheet-like member held in abutting contact with said rotary press member and impregnated with liquid, said sheet-like member being moveable while held in abutting contact with said rotary press member.

With such a stencil printing machine, the effect of the invention as defined in claim 9 is obtained and, in addition, the sheet-like member, impregnated with liquid, enables to be brought into abutting contact with the

rotary press member at variable positions.

Another important feature of the invention as defined in claim 15 concerns the stencil printing machine, defined in claim 9, wherein said liquid application unit comprises a biasing member held in abutting contact with said rotary press member and impregnated with liquid which is retained in said biasing member, and a liquid supply unit for supplying liquid to the outer circumferential periphery of said rotary press member at a point upstream of said biasing member in a direction which said rotary press member rotates.

With such a stencil printing machine, the effect of the invention as defined in claim 9 is obtained and, in addition, liquid is first supplied to the rotary press member with the liquid supply unit and is then smoothly applied over the outer circumferential periphery of the rotary press member with the biasing member, enabling adjustment of the amount of liquid to be applied to the rotary press member with the liquid supply unit.

Another important feature of the invention as defined in claim 16 concerns the stencil printing machine, defined in claim 9, wherein said liquid application unit comprises a sheet-like member held in abutting contact with said rotational press member at an adjustable contact area and moveable to vary the position of said adjustable contact area, and a liquid supply unit for supplying liquid to the outer circumferential periphery of said rotary press member at a point upstream of said adjustable contact area of said sheet-like member in a direction which said rotary press member rotates.

With such a stencil printing machine, the effect of the invention as defined in claim 9 is obtained and, in addition, liquid is first supplied to the rotary press member with the liquid supply unit and is then smoothly applied over the outer circumferential periphery of the rotary press member with the sheet-like member which can be brought into abutting contact with the rotary press member at variable positions, thereby enabling adjustment of the amount of liquid to be applied to the rotary press member with the liquid supply unit.

Another important feature of the invention as defined in claim 17 concerns the stencil printing machine which has two sets of printing sections located at an upstream side and a downstream side, respectively, and each

composed of a rotary printing drum with an outer circumferential periphery to which a stencil sheet is mounted and a rotary press member which is movable between a pressurized position to be pressed against the outer circumferential periphery of the printing drum and a separated position to be separate from the outer circumferential periphery, a paper feed section for feeding print medium to the printing section at the upstream side, and an upstream transfer mechanism for transferring and feeding print medium, discharged from the printing section at the upstream side, to the printing section at the downstream side, wherein print medium, fed from the paper feed section to the printing section at the upstream side, is pressed between and transferred by the printing drum at the upstream side and the rotary press member both of which are rotated together, and during such a pressurized and transfer movement of print medium, one surface of print medium is transferred with ink and print medium is then fed to the printing section at the downstream side with the upstream transfer mechanism to allow print medium to be pressurized between and transferred by the printing drum and the rotary press member at the downstream side such that during such a pressurized and transfer movement, the other surface of print medium is transferred with ink to perform a double-phase printing operation, and which comprises at least said rotary press member, located at the downstream side, including an outer circumferential periphery formed with micro-convexities and micro-concavities.

With such a stencil printing machine, contamination of print medium is prevented only by providing the micro-convexities and the micro-concavities over the outer circumferential periphery of at least the rotary press member, located at the downstream side. In particular, at least the downstream rotary press member has a decreased contact surface area with the non-fixed ink area. Accordingly, when the rotary press member is separated from print medium, since the rotary press member is not adhered with non-fixed ink, it is possible for the non-fixed ink from being adhered to the rotary press member.

Another important feature of the invention as defined in claim 18 concerns the stencil printing machine wherein said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press

member has a depth of a value above 0.035 mm.

With such a stencil printing machine, the effect of the invention defined in claim 17 is obtained and, in addition, when the rotary press member presses the printing drum via print medium, there is a big difference in level in the convexities and the concavities to interrupt the concavities from being practically brought into contact with non-fixed ink of print medium, thereby adequately minimizing transfer of non-fixed ink to the rotary press member.

Another important feature of the invention as defined in claim 19 concerns the stencil printing machine wherein said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press member has a depth of a value above 0.044 mm.

With such a stencil printing machine, the effect of the invention defined in claim 17 is obtained and, in addition, when the rotary press member presses the printing drum via print medium, there is an adequately big difference in level in the convexities and the concavities such that the concavities have little or no contact with non-fixed ink of print medium, thereby further minimizing transfer of non-fixed ink to the rotary press member.

Another important feature of the invention as defined in claim 20 concerns the stencil printing machine defined in claims 17 to 19 wherein a distance between apexes of said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press member has a value below 0.64 mm.

With such a stencil printing machine, the effects of the invention defined in claims 17 to 19 is obtained and, in addition, when the rotary press member presses the printing drum via print medium, there is a narrow distance between the convexities and the concavities formed over the outer circumferential periphery of the rotary press member, interrupting the print image from appearing a visible convexity and concavity pattern.

Another important feature of the invention as defined in claim 21 concerns the stencil printing machine defined in any one of preceding claims 17 to 20 wherein said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press member are composed of

point-like convexities and concavities.

With such a stencil printing machine, the effects of the invention as defined in claims 17 to 20 are obtained and, in addition, the convexities and the concavities can be uniformly formed in either direction over the outer circumferential periphery of the rotary press member.

Another important feature of the invention as defined in claim 22 concerns the stencil printing machine defined in any one of preceding claims 17 to 20 wherein said micro-convexities and said micro-concavities of the outer circumferential periphery of said rotary press member are composed of line-shaped convexities and concavities which are orientated in the same direction as that which print medium is transferred.

With such a stencil printing machine, the effects of the invention as defined in claims 17 to 20 are obtained and, in addition, the convexities and the concavities can be regularly and distinctly formed over the outer circumferential periphery of the rotary press member in a direction perpendicular an axial direction thereof.

Another important feature of the invention as defined in claim 23 concerns the stencil printing machine, defined in claim 17, which further comprises a liquid application unit for applying liquid to the outer circumferential periphery of said rotary press member.

With such a stencil printing machine, the effect of the invention as defined in claim 17 is obtained and, in addition, during separating movement between the rotary press member and print medium, a non-fixed ink area is not split whereas a liquid area is split, thereby preventing non-fixed ink from being adhered to the rotary press member.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic structural view of a stencil printing machine of a prior art;

FIG. 2 is a view for illustrating a condition experienced in the prior art wherein during a separating movement of a press roller and a print sheet, a non-fixed ink area is split to cause ink to be transferred to the press roller;

FIG. 3 is a schematic structural view of a stencil printing machine of a preferred embodiment according to the present invention;

FIG. 4 is a view illustrating an evaluated result in terms of a contaminated status and an image quality which is attained in a first preferred embodiment (wherein a downstream press roller has an outer circumferential periphery formed with micro-convexities and concavities and wherein the press roller is not applied with silicone oil with a liquid application roller) of the present invention;

FIG. 5 is a view illustrating the evaluated result in terms of the contaminated status and the image quality which is attained in a second preferred embodiment (wherein the downstream press roller has the outer circumferential periphery formed with the micro-convexities and concavities and wherein the press roller is slightly applied with silicone oil with the liquid application roller) of the present invention;

FIG. 6 is a view illustrating the evaluated result in terms of the contaminated status and the image quality which is attained in a third preferred embodiment (wherein the downstream press roller has the outer circumferential periphery formed with the micro-convexities and concavities and wherein the press roller is applied with silicone oil with the liquid application roller) of the present invention;

FIG. 7 is a view illustrating the evaluated result in terms of the contaminated status and the image quality which is attained in a comparison (wherein the downstream press roller is made of natural rubber material and has an outer circumferential periphery with a flat surface without the micro-convexities and concavities and wherein the press roller is not applied with silicone oil with the liquid application roller) of the present invention;

FIG. 8 is a view for illustrating a condition wherein during the separating movement of the press roller and the print sheet, silicone oil applied to the press roller is split and separated;

FIG. 9 is a perspective view of a press roller of a fourth preferred embodiment according to the present invention;

FIG. 10 is a perspective view of a press roller of a fifth preferred embodiment according to the present invention;

FIG. 11 is a typical view for illustrating a difference in level of the convexities and the concavities of the press rollers in the fourth and fifth preferred embodiments of the present invention;

FIGS. 12A and 12B show a detailed structure of a fourth preferred embodiment according to the present invention, wherein FIG. 12A is a front view of the press roller and FIG. 12B is an enlarged cross sectional view of a part of the structure shown in FIG. 12A;

FIGS. 13A and 13B show another detailed structure of a fifth preferred embodiment according to the present invention, wherein FIG. 13A is a front view of the press roller and FIG. 13B is an enlarged cross sectional view of a part of the structure shown in FIG. 12A;

FIGS. 14A and 14B show a structure of the sixth preferred embodiment according to the present invention, wherein FIG. 14A is an overall structural view of a liquid application unit and FIG. 14B is a schematic perspective view of the liquid application unit;

FIG. 15 is a schematic structural view of a liquid application unit of a seventh preferred embodiment according to the present invention;

FIG. 16 is a schematic structural view of a liquid application unit of an eighth preferred embodiment according to the present invention; and

FIG. 17 is a schematic structural view of a liquid application unit of a ninth preferred embodiment according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

To describe the present invention, preferred embodiments of the present invention will be described below with reference to the drawings.

FIG. 3 shows a schematic whole structural view of a stencil printing machine of first to third preferred embodiments according to the present invention, and a common structure of the first to third preferred embodiments is described below with reference to FIG. 3.

As shown in FIG. 3, the digital type stencil printing machine 1 is mainly constructed of an original read out section which is not shown, an upstream stencil making section 2, a downstream stencil making section 3, an upstream printing section 4, a downstream printing section 5, a paper feed section 6, an

upstream belt transfer unit 7, a downstream belt transfer unit 8, a sheet discharge section 9, an upstream stencil disposal section 10 and a downstream stencil disposal section 11.

5 The original read out section includes, for example, an automatic paper feed and read out unit. The automatic paper feed and read out unit is constructed of an inclined original resting plate to allow the original to be rested, an original feed roller pair for transferring the original resting on the inclined original resting plate, and a line image sensor for obtaining image data by converting contents of the original, which is transferred, to a train of
10 electric signals. The line image sensor is commonly used as that of the original positioning and read out unit.

The original positioning and read out unit includes a horizontal original positioning glass table for allowing the original to be positioned, a pressure plate located on the horizontal original positioning glass table for free opening and closing capabilities, a guide belt located in an area below the horizontal
15 original positioning glass plate to be moveable with a drive force of a pulse motor, and the line image sensor which is guided with the guide belt to move in the area below the original positioning glass plate.

Further, the line image sensor of the automatic paper feed and read out
20 unit reads out the original which is transferred with the original feed roller pair. In the original positioning and read out unit, the line image sensor is guided and moved with the guide belt to scan a lower surface of the original to read out the contents of the original.

The upstream stencil making section 2 includes a stencil sheet receiving
25 tray 21 which receives an elongated stencil sheet 20 in the form of a roll, a thermal printing head 22 composed of a writing head which is located at a position downstream of the stencil sheet receiving tray 21 in a transfer direction of the stencil sheet 20 relative to the stencil sheet receiving tray 21, a platen roller 23 located in opposed relation to the thermal printing head 22 and driven by a pulse motor (not shown), a stencil feed roller pair 24 located
30 downstream of the thermal printing head 22 and the platen roller 23 in the transfer direction of the stencil sheet 20 and rotated with the drive force of the pulse motor (not shown), a stencil feed roller pair 25 located further

downstream of the stencil feed roller pair 24 in the transfer direction of the stencil sheet, and a stencil cutter 26 located downstream of the stencil feed roller pair 25. The thermal printing head 22 includes a plurality of dot-shaped thermal elements located, in a plane perpendicular to the transfer direction of the stencil sheet 20, to occupy a space in a range equal to a paper size of A3 to meet the maximum size A3 of a print sheet which is intended in the preferred embodiment.

In addition, rotations of the platen roller 23 and the stencil feed roller pair 24 allow the stencil sheet 20 to be transferred. During such transfer of the stencil sheet 20, the dot-shaped thermal elements of the thermal printing head 22 are selectively activated to produce heat on the basis of image data, which corresponds to an upper surface (one surface) of the original, read out with the line image sensor to permit thermal perforation in the stencil sheet 20 to form a desired perforated area, with a trailing edge of the stencil sheet 20, which has the desired perforated area, being cut with the stencil cutter 26 to form a perforated stencil sheet 20 of a given length.

The downstream stencil making section 3 includes a stencil sheet receiving tray 3 which receives an elongated stencil sheet 20 in the form of a roll, a thermal printing head 32 composed of a writing head which is located at a position downstream of the stencil sheet receiving tray 3 in a transfer direction of the stencil sheet 20 relative to the stencil sheet receiving tray 3, a platen roller 33 located in opposed relation to the thermal printing head 32 and driven by a pulse motor which is not shown, a stencil feed roller pair 34 located downstream of the thermal printing head 32 and the platen roller 33 in the transfer direction of the stencil sheet 20 and rotated with the drive force of the pulse motor which is not shown, a stencil feed roller pair 35 located further downstream of the stencil feed roller pair 34 in the transfer direction of the stencil sheet, and a stencil cutter 36 located downstream of the stencil feed roller pair 35. The thermal printing head 32 includes a plurality of dot-shaped thermal elements located, in a plane perpendicular to the transfer direction of the stencil sheet 20, to occupy a space in a range equal to a paper size of A3 to meet the maximum size A3 of a print sheet which is intended in the preferred embodiment.

In addition, rotations of the platen roller 33 and the stencil feed roller pair 34 allow the stencil sheet 20 to be transferred. During such transfer of the stencil sheet 20, the dot-shaped thermal elements of the thermal printing head 32 are selectively activated to produce heat on the basis of image data, which corresponds to a lower surface (the other surface) of the original, read out with the line image sensor to permit thermal perforation in the stencil sheet 20 to form a desired perforated area, with a trailing edge of the stencil sheet 20, which has the desired perforated area, being cut with the stencil cutter 36 to form a perforated stencil sheet 20 of a given length.

The upstream printing section 4 is constructed of an upstream printing drum 40 which includes an outer peripheral wall 40a, which is composed of an ink permeable member formed in a perforated structure, and which rotates in a direction as shown by an arrow A in FIG. 3 with a drive force of a main motor which is not shown in FIG. 3, and a stencil clamping segment 41 mounted to the outer periphery 40a of the printing drum 40 for clamping a leading edge of the stencil sheet 20.

Further, the upstream printing section 4 includes a squeegee roller 42 located inside the outer peripheral wall 40a and held in contact with an inner peripheral surface of the outer peripheral wall 40a, a doctor roller 43 spaced from the squeeze roller 42 with a given gap and an ink supply unit 44 for supplying ink to an area between the rollers 42, 43, a press roller 46 which is located in an area outside the printing drum 40 in opposed relation to the squeeze roller 42 via the outer peripheral wall 40a thereof and which serves as a rotating press member, and a pressure exerting unit (not shown) which selectively moves the press roller 46 into a pressured engagement position (a position as indicated by a solid line in FIG.3) to urge the press roller 46 against the outer peripheral wall 40a of the printing drum 40, and a separated position (a position indicated by a phantom line in FIG. 3) to separate the press roller 46 from the outer peripheral wall 40a of the printing drum 40. The press roller 46 functions to move between the pressured engagement position and the separated position in association with rotation of the printing drum 40 during the printing operation such that, during transit of the print sheet 45, which serves as print medium, transferred in synchronism with

rotation of the printing drum 40, the press roller 46 remains in the pressured engagement position and, during other operating phase (i.e., during non-transit phase of the print sheet 45), the press roller 46 remains in the separated position.

5 With such a structure, clamping the leading edge of the stencil sheet 20, which is transferred from the upstream stencil making section 2, with the stencil clamping segment 41, while permitting rotation of the printing drum 40 under the clamped state of the stencil sheet 20 allows the stencil sheet 20 to be wound around and mounted to the outer periphery 40a of the printing drum 40. When this occurs, the print sheet 45, which is transferred in
10 synchronism with the rotation of the printing drum 40, is brought into pressured contact with the stencil sheet 20 of the printing drum 40 with the action of the press roller 46, allowing ink to be transferred through the perforated area of the stencil sheet 20 onto the upper surface (the one surface)
15 of the print sheet 45 to reproduce a desired image thereon.

20 The downstream printing section 5 is constructed of a downstream printing drum 50 that includes an outer peripheral wall 50a composed of an ink permeable member formed in a perforated structure and that rotates in a direction as shown by an arrow B in FIG. 3 with a drive force of a main motor which is not shown, and a stencil clamping segment 51 mounted to the outer periphery 50a of the printing drum 50 for clamping a leading edge of the stencil sheet 20.

25 Further, the upstream printing section 5 includes a squeegee roller 52 located inside the outer peripheral wall 50a and held in contact with an inner peripheral surface of the outer peripheral wall 50a, a doctor roller 53 spaced from the squeeze roller 52 with a given gap, an ink supply unit 54 for supplying ink to an area between the rollers 52, 53, a downstream press roller 56 which is located in an area outside the printing drum 50 in opposed relation to the squeeze roller 52 via the outer peripheral wall 50a thereof and
30 which serves as a rotary press member, a pressure exerting unit (not shown) which selectively moves the press roller 56 into a separated position (a position as indicated by a solid line in FIG.3) to urge the press roller 56 against the outer peripheral wall 50a of the printing drum 50 and a pressured

position (a position indicated by a phantom line in FIG. 3) to separate the press roller 56 from the outer peripheral wall 50a of the printing drum 50, and a liquid application roller (a liquid application unit) 70 which enables application of silicone oil, which is liquid, to an outer periphery of the press roller 56. The press roller 56 functions to move between the pressured engagement position and the separated position in association with rotation of the printing drum 50 during the printing operation such that, during transit phase of the print sheet 45, which serves as print medium, transferred in synchronism with rotation of the printing drum 50, the press roller 56 remains in the pressured engagement position and, during other operating phase (i.e., during non-transit phase of the print sheet 45), the press roller 56 remains in the separated position. The liquid application roller 70 may be associated with the press roller 56 so as to rotate therewith, or may be located (in a fixed state) so as to interrupt rotation with the press roller 56.

With such a structure, clamping the leading edge of the stencil sheet 20, which is transferred from the upstream stencil making section 3, with the clamping base 51, while permitting rotation of the printing drum 50 under the clamped state of the stencil sheet 20 allows the stencil sheet 20 to be wound around and mounted to the outer periphery 50a of the printing drum 50. When this occurs, the print sheet 45, which is transferred in synchronism with the rotation of the printing drum 50, is brought into pressured contact with the stencil sheet 20 of the printing drum 50 with the action of the press roller 56, allowing ink to be transferred through the perforated area of the stencil sheet 20 onto the lower surface (the other one surface) of the print sheet 45 to reproduce a desired image thereon.

The paper feed section 6 is constructed of a paper feed tray 57 on which a stack of the print sheets 45, which serve as printing media, is placed, a primary paper feed roller pair 58 for moving only one print sheet 45 from the uppermost position of the stack of the print sheets 45 in the paper feed tray 57, and a secondary paper feed roller pair 59 for transferring the print sheet 45, which is transferred with the paper feed roller pair 58, to an area between the printing drum 40 and the press roller 46 in synchronism with the rotation of the upstream printing drum 40. The primary and secondary paper feed roller

pairs 58, 59 are so arranged as to be selectively applied with the drive force of the main motor by means of respective paper feed clutches which is not shown.

The upstream belt-conveyer transfer unit 7, which serves as the upstream transfer mechanism, functions to receive the print sheet 45 discharged from the upstream printing section 4 to transfer the received print sheet 45 to an area in front of the downstream printing section 5 to be fed thereto. The upstream belt-conveyer transfer unit 7 includes a pair of belt stretching members 60a, 60b, a belt 62 stretched between the pair of belt stretching members 60a, 60b, an intake box 63 and an intake fan 64 for sucking the leading edge of the print sheet 45 transferred on the belt 62, and a belt drive unit which is not shown to drive the belt 62 for rotating movement of the belt stretching member 60a (or 60b). Further, the upstream belt-conveyer transfer unit 7 functions to suck the print sheet 45 to transfer the print sheet 45 due to the movement of the belt 62 per se under a condition that the surface of the print sheet 45 opposed to the previously printed surface is held in contact with the belt 62.

The downstream belt-conveyer transfer unit (the upstream transfer unit) 8 function to receive the print sheet 45 discharged from the downstream printing section 5 to transfer the received print sheet 45 to the sheet discharge section 9. The downstream belt-conveyer transfer unit 8 includes a pair of pulleys 66a, 66b, a belt 67 stretched between the pair of pulleys 60a, 60b, an intake box and an intake fan, both of which are not shown, for sucking the leading edge of the print sheet 45 transferred on the belt 67, and a belt drive unit (not shown) to drive the belt 67 for rotating movement of the pulley 66a (or 66b). Further, the downstream belt-conveyer transfer unit 8 functions to suck the print sheet 45 to transfer the print sheet 45 due to the movement of the belt 67 per se.

The sheet discharge section 9 includes a paper receiving tray 71 located in a drop area of the print sheet 45 for allowing the print sheet 45, which has been printed and is transferred with the downstream belt-conveyer transfer mechanism 8, to be placed in a stacked state.

The upstream stencil disposal section 10 includes a stencil separating

roller pair 72 for receiving the leading edge of the stencil sheet 20, which has been previously wound on the upstream printing drum 40 with the leading edge being released from the upstream printing drum 40, and for transferring the stencil sheet 20, whose clamped state is released, while peeling off the same from the upstream printing drum 40, and a stencil disposal box 73 for receiving the stencil sheet 20 which is transferred with the stencil separating roller pair 72.

The downstream stencil disposal section 11 includes a stencil separating roller pair 74 for receiving the leading edge of the stencil sheet 20, which has been previously wound on the downstream printing drum 50 with the leading edge being released from the downstream printing drum 50, and for transferring the stencil sheet 20, whose clamped state is released, while peeling off the same from the downstream printing drum 50, and a stencil disposal box 75 for receiving the stencil sheet 20 which is transferred with the stencil separating roller pair 74.

The structure described above is common to the first to third preferred embodiments, and the first to third preferred embodiments of the digital type stencil printing machine of the present invention will be described below in detail in conjunction with structures which are different from each other.

In the first preferred embodiment, as shown in FIG. 8, an outer circumferential periphery 56a of the downstream press roller 56 has micro-convexities and concavities which are not shown and the outer circumferential periphery 56a of the press roller 56 is not applied with silicone oil from the liquid application roller 70. The micro-convexities and concavities of the outer circumferential periphery 56a of the press roller 56 is formed by mounting a mesh screen, made of polyester, with distances between adjacent apexes of the micro-convexities and concavities and depths of the same being varied as seen in FIG. 4.

Here, an intersecting point between fibers of the polyester mesh screen is regarded as the apex of the convexities and the concavities. Distance data between the adjacent apexes is indicated with a calculated value obtained by calculating the mesh number of the polyester mesh screen, and depth data of the convexities and the concavities is indicated with an experimental result by

measuring a difference in level between the warp and the woof of the fabric with a contact type surface roughness meter. The reason why the depth of the convexities and the concavities is actually measured in the above method is described below. When using the polyester mesh screen, there are some instances wherein the mesh screen is hardly protected from contamination due to an inherent structure thereof. When an adequate protection effect is obtained, a non-fixed ink area of the print sheet is brought into contact only with the intersecting point area of the fabric corresponding to the apex area of the convexities and the concavities. When this occurs, if the non-fixed ink area is brought into contact with other areas than the intersecting point area of the fabric with a small difference in level between the warp and the woof of the fabric at the intersecting area, it is difficult for the mesh screen to have the contamination protecting effect. For this reason, the difference in level of the warp and the woof at the intersecting point of the fabric is regarded as the depth of the convexities and the concavities. This is also applied in the second and third preferred embodiments which will be discussed later.

In the second preferred embodiment, the outer circumferential periphery 56a of the downstream press roller 56 has the micro-convexities and concavities which are not shown and the outer circumferential periphery 56a of the press roller 56 is slightly applied with the silicone oil with a certain viscosity from the liquid application roller 70. The convexities and the concavities of the outer circumferential periphery 56a of the press roller 56 are formed by mounting the mesh screen, made of polyester, which is selected from a number of mesh sizes with different distances between adjacent apexes of the convexities and the concavities and different depths of the convexities and the concavities with a fixed level in the viscosity of silicone oil as seen in FIG. 5.

In the third preferred embodiment, the outer circumferential periphery 56a of the downstream press roller 56 has the micro-convexities and concavities which are not shown and the outer circumferential periphery 56a of the press roller 56 is applied with the silicone oil from the liquid application roller 70. The convexities and the concavities of the outer circumferential periphery 56a of the press roller 56 is formed by mounting the

mesh screen, made of polyester, with fixed values in distances between adjacent apexes of the convexities and the concavities and in depths of the convexities and the concavities while the viscosity of silicone oil has different values as seen in FIG. 6.

5 In a comparison (in prior art), further, the downstream press roller 56 is made of natural rubber material and has an outer circumferential surface formed with a flat surface without the micro-convexities and concavities as seen in FIG. 7, and the press roller 56 is not applied with liquid such as silicone oil from the liquid application roller 70.

10 Now, the stencil making operation and the printing operation of the aforementioned stencil printing machine 1 is described. When a stencil making mode is selected, the controller checks whether the stencil sheets 20 are wound on respective printing drums 40,50, and in the presence of the stencil sheets 20 over the printing drums, the controller allows the stencil sheets 20 to be removed from the respective printing drums 40,50 to discharge them in the stencil disposal boxes 73, 75, respectively.

15 Upon completion of the stencil disposal step, the stencil sheet 20 is thermally perforated with the thermal printing head 22 on the basis of image data correlated with an upper surface side read out by the original read out operation. Then, a mounting step is carried out for mounting the stencil sheet 20, which is made, onto the upstream side printing drum 40, thereby terminating the stencil making operation at the upstream side. Likewise, the stencil sheet 20 is also thermally perforated with the thermal printing head 32 on the basis of image data correlated with a lower surface side read out by the original read out operation. Then, a mounting step is carried out for mounting the stencil sheet 20, which is made, onto the downstream side printing drum 50, thereby terminating the stencil making operation at the downstream side.

25 Next, when selecting the printing mode, the operator checks whether the print sheet 45 remains on the paper feed tray 57, and in the absence of the print sheet 45, the controller carries out the non-print sheet error correction. Further, the controller checks whether the stencil sheets 20 are wound on the respective printing drums 40, 50 and in the absence of the stencil sheets 20, the controller carries out the non-stencil sheet error correction. Also, the

controller checks whether ink remains in the ink traps between the squeeze rollers 42, 52 and between the doctor rollers 43, 53, and in the absence of ink, the controller performs the non-ink error correction.

When clearing all the check items, the main motor is driven to rotate the
5 respective printing drums 40, 50, causing the print sheet 45 to be fed to the
printing drum 40 at the upstream side from the paper feed section 6 in
synchronism with the rotation of the main motor. The print sheet 45, thus fed
to the printing drum 40, is urged toward the stencil sheet 20 of the printing
10 drum 40 by means of the press roller 46 to allow ink image to be transferred
to the upper surface of the print sheet 45. The print sheet 45, thus printed at its
upper surface, is peeled off from the outer circumferential periphery of the
printing drum 40 and is guided to the upstream belt transfer mechanism 7.
The upstream belt transfer mechanism 7 transfers the print sheet 45 with its
15 lower surface held in contact with the belt 62 to allow the print sheet 45 to the
downstream printing drum 50 from the downstream site of the belt 62. The
print sheet 45 is then urged toward the stencil sheet 20 of the printing drum 50
with the press roller 56 via the belt 67 to allow ink image to be transferred to
the lower surface of the print sheet 45. The print sheet 45, whose lower
20 surface is printed, is peeled off from the outer circumferential periphery of the
printing drum 50 and is guided to the downstream belt transfer mechanism 8.
The downstream belt transfer mechanism 8 allows the print sheet 45 to be
transferred with the belt 67, thereby discharging the print sheet 45 to be
discharged to the sheet discharge tray 71. The print sheet 45 discharged into
the sheet discharge tray 71 is accumulated here in stacked form.

25 The double-face printing operation has been carried out in conjunction
with the first to third preferred embodiments and the comparison to obtain
experimental results shown in FIGS. 4 to 7 in terms of the contaminated
status of the print sheet 45 and the press roller 56 and an image quality of the
lower surface of the print sheet 45. In FIGS. 4 to 7, a visual evaluation
30 standard for the contaminated status involves ©: an event wherein
no-contamination on the print sheet 45 and ink is hardly adhered to the outer
circumferential periphery 56a of the press roller 56, ○: an event wherein
although the print sheet 45 has a little contamination, the outer

circumferential periphery 56a of the press roller 56 is slightly adhered with ink, Δ : an event wherein the print sheet 45 has a slight contamination, and \times : an event wherein the print sheet 45 is considerably contaminated. The visual evaluation standard for the image quality at the lower surface of the print sheet 45 involves \bigcirc : an event wherein beautiful print is carried out in uniform state, and \times : an event wherein a convexity and concavity pattern of the press roller 56 is confirmed.

An evaluation result between the first preferred embodiment and the comparison reveals an improvement in the contaminated status because of the provision of the micro-convexities and concavities formed over the outer circumferential periphery 56a of the press roller 56. That is, forming the tiny unevenness over the outer circumferential periphery 56a of the press roller 56 results in a minimized contact area between the outer circumferential periphery 56a of the press roller 56 and a non-fixed ink surface of the print sheet 45 to avoid the press roller 56 from being adhered with non-fixed ink at an area corresponding to a portion wherein the press roller 56 remains out of contact when the press roller 56 is separated from the print sheet 45. For this reason, it seems that non-fixed ink is not appreciably adhered to the press roller 56 and, therefore, the contamination of the print sheet 45 is avoided with a little decrease in a print density of the print sheet. Also, the contamination of the print sheet 45 can be prevented with the provision of mere micro-convexities and concavities formed over the outer circumferential periphery 56a of the press roller 56, with a resultant capability in preventing the contamination with a simplified structure. It will thus be seen that it is possible for the stencil printing machine to prevent the print sheet from being contaminated with the little reduction in the print density of the print sheet 45 in the simplified structure.

In view of the evaluation result of the first preferred embodiment, further, it is possible to appreciably preclude the contamination of the print sheet 45 (as evaluated as \bigcirc in the contaminated status) with the uneven surface having a value beyond the order of 0.035 mm in depth, of the outer circumferential periphery 56a of the press roller 56. That is, when the press roller 56 urges the printing drum 50 via the print sheet 45, the outer

circumferential periphery 56a of the press roller 56 has an increased difference in level of the convexities and the concavities of the outer circumferential periphery 56a of the press roller 56 such that the convex portion of the convex and concave area is precluded to be hardly held in contact with the non-fixed ink of the print sheet 45. When this occurs, since a level of transfer of non-fixed ink relative to the press roller 56 can be adequately minimized, it appears that a visible contamination of the print sheet 45 is reliably precluded.

In view of the evaluation result of the second preferred embodiment, further, it is possible to appreciably preclude the contamination of the print sheet 45 (as evaluated as ◎ in the contaminated status) with the convexities and the concavities having a value beyond the order of 0.044 mm in depth, of the outer circumferential periphery 56a of the press roller 56. That is, when the press roller 56 urges the printing drum 50 via the print sheet 45, the outer circumferential periphery 56a of the press roller 56 has an appreciably increased difference in level of the convexities and the concavities of the outer circumferential periphery 56a of the press roller 56 such that the convex portion of the convex and concave area has little or no contact with the non-fixed ink area of the print sheet 45. When this occurs, since a level of transfer of non-fixed ink relative to the press roller 56 can be adequately minimized, it appears that a visible contamination of the print sheet 45 is more reliably precluded.

In view of the evaluation results of the first and second preferred embodiments, it is possible for the print sheet 45 to be printed in a uniform and beautiful fashion at the rear side (as evaluated as ○ in the image quality) with the convexities and the concavities having a value below the order of 0.64 mm in the distance between the adjacent apexes, of the outer circumferential periphery 56a of the press roller 56. That is, when the press roller 56 urges the printing drum 50 via the print sheet 45, the outer circumferential periphery 56a of the press roller 56 has a narrow space between the adjacent apexes in the convex and concave area of the outer circumferential periphery 56a of the press roller 56 such that a visible uneven pattern does not appear on the print image. For this reason, it is thought that a

high quality image is obtained.

In view of the evaluation result of the second preferred embodiment, application of silicone oil over the outer circumferential periphery 56a of the press roller 56 has an effect for precluding the contamination of the print sheet 45. That is, as shown in FIG. 8, when the press roller 56 and the print sheet 45 are separated from one another, the non-fixed ink portion a is not ripped and the liquid portion b is ripped, precluding the press roller 56 from being adhered with the non-fixed ink a to prevent the contamination of the print sheet 45 in a substantially complete fashion.

In view of the evaluation result of the third preferred embodiment, if silicone oil with the viscosity in the order below 1000 millipascal·second (mPa·s) is used, the print sheet 45 can be hardly contaminated (as evaluated as ○ in the contaminated status). That is, it is thought that when the press roller 56 and the print sheet 45 are separated from one another, liquid is reliably split at a low viscosity liquid portion for preventing non-fixed ink from being adhered to the press roller 56 to completely preclude the contamination of the print sheet 45.

In view of the evaluation result of the third preferred embodiment, if silicone oil with the viscosity in the order below 500 millipascal·second (mPa·s) is used, the contamination of the print sheet can be precluded (as evaluated as ◎ in the contaminated status). That is, it is thought that when the press roller 56 and the print sheet 45 are separated from one another, liquid is more reliably split at a lower viscosity liquid portion for preventing non-fixed ink from being adhered to the press roller 56 to further completely preclude the contamination of the print sheet 45.

To summarize the evaluation results of the first to third preferred embodiments, it is preferably advisable that the uneven surface of the outer circumferential periphery 56a of the press roller 56 has the space between the adjacent apexes in a value ranging from 0.10 to 0.64 mm, the depth in a value ranging from 0.035 (preferably 0.044) to 0.20 mm and the press roller 56 is preferably applied with silicone oil with the density in a value below 500 millipascal·second.

Now, a detailed description will be given to fourth to ninth preferred

embodiments of the present invention. Overall structures of the stencil printing machines are identical with those of the structures of the first to third preferred embodiments commonly shown in FIG. 1 and, therefore, a detailed description of the same is herein omitted except for component parts which are different from those of the first to third preferred embodiments.

In the fourth and fifth preferred embodiments, micro-convexities and concavities formed over the outer circumferential periphery 56a of the downstream press roller 56 have respective detailed structures discussed below.

The micro-convexities and concavities of the fourth preferred embodiment shown in FIG. 9 are formed of point-like micro-convexities and concavities composed of a large number of point-like segments 77 located on the outer circumferential periphery 56a. The micro-convexities and concavities of the fifth preferred embodiment shown in FIG. 10 are formed of line-shaped micro-convexities and concavities composed of a large number of line-shaped segments 79 located on the outer circumferential periphery 56a. The respective line-shaped protrusions 79 are orientated in a circumferential direction of the press roller 56, i.e. in the same direction (a direction perpendicular to an axial direction of the press roller 56) as that which the print sheet 45 is transferred.

FIG. 11 is an enlarged typical view illustrating the point-like segments 77 and the line-shaped segments 79 as viewed along respective lines N-N of FIGS. 9 and 10. As shown in FIG. 11, assuming that the distance between the apexes a1 and a2 of the point-like segments 77 or the line-shaped segments 79 is represented with A, the height between the apex a1 (or the apex a2) and the lowest bottom wall b, i.e., the depth of the convexities and the concavities, is represented with B, the dimensions A and B correspond to the dimensions described with reference to the first to third preferred embodiments. In particular, the dimension A, which corresponds to the distance between the adjacent convexities and concavities, is preferably designed to be in a range below 0.64 mm. The dimension B, which corresponds to the depth between the convexities and the concavities, is preferably designed to be in a range above 0.035 mm and more preferably in a range above 0.045 mm.

In the fourth preferred embodiment, the presence of the convexities and the concavities are substantially equally distributed in any direction over the outer circumferential periphery 56a of the press roller 56 substantially evenly enables protection of ink transfer in every directions.

5 In the fifth preferred embodiment, the presence of the line-shaped convexities and concavities, which are formed over the outer circumferential periphery 56a of the press roller 56 on a regular basis in the same direction as that which the print sheet 45 is transferred, ensures preclusion of ink transfer that would otherwise occur in a direction perpendicular to the axial direction
10 of the press roller 56.

Although the line-shaped segments 79 of the fifth preferred embodiment are orientated in the same direction as that which the print sheet 45 is transferred, the line-shaped segments 79 may be orientated in a spiral direction or may be orientated at an inclined angle with respect to the transfer direction of the print sheet 45 in either direction. Further, the presence of the line-shaped segments 79 formed in either direction enables preclusion of ink transfer with respect to the direction perpendicular to that the line-shaped segments 79 are orientated in a reliable manner.
15

The point-like convexities and concavities of the fourth preferred embodiment is actually formed by a process shown in FIGS. 12A and 12B and a process shown in FIGS. 13A and 13B.
20

In FIGS. 12A and 12B, the point-like convexities and concavities are formed by covering the outer circumferential periphery 56a of the press roller 56 with a cylindrical screen mesh 80 or by adhering the screen mesh 80 to the outer circumferential periphery 56a of the press roller 56. That is, this structure corresponds to those used in the first to third preferred embodiments. In FIGS. 13A and 13B, the point-like convexities and concavities are formed by adhering a large number of spherical bodies 81, serving as the point-like segments, to the outer circumferential periphery 56a of the press roller 56 by means of adhesive material 82.
25
30

The detailed example shown in FIGS. 12A and 12B enables the formation of the micro-convexities and concavities by preparing the screen mesh 80 per se separately from the press roller 56 and subsequently locating

the screen mesh onto the outer circumferential periphery 56a of the press roller 56 in a covering method or in the adhering method, providing an ease of formation of the point-like convexities and concavities.

The detailed example shown in FIGS. 13A and 13B enables the formation of the micro-convexities and concavities by preparing the large number of spherical bodies 81 per se separately from the press roller 56 and subsequently locating the spherical bodies onto the outer circumferential periphery 56a of the press roller 56 in the adhering method, providing an ease of formation of the point-like convexities and concavities.

In the sixth to ninth preferred embodiments, the liquid application units for applying liquid to the outer circumferential periphery 56a of the downstream press roller 56 have detailed structures which are constructed in a manner described below.

The liquid application unit 83A of the sixth preferred embodiment shown in FIGS. 14A and 14B is constructed of a liquid application roller 84 held in pressured contact with the press roller 56 for rotating movement, a liquid supply pipe 85 concentrically located in an inner peripheral position of the liquid application roller 84 and internally filled with liquid, and a porous sheet 86 such as a nonwoven fabric, etc. interposed between the outer periphery of the liquid supply pipe 85 and the inner periphery of the liquid application roller 84. The liquid supply pipe 85 is formed with a large number of apertures 85a through which liquid in the liquid supply pipe 85 flows to permeate into the porous sheet 86, with permeated liquid being fed to the outer periphery of the liquid application roller 84. Thus, the liquid supply pipe 85 and the porous sheet 86 forms a liquid supply section.

With such a sixth preferred embodiment, the liquid application roller 84 rotates with the press roller 56 to apply liquid onto the press roller 56, making it possible to apply liquid to the press roller 56 with little rotational load. Also, the presence of a structure to rotate the liquid application roller 84 substantially completely eliminates the rotational load to be exerted to the press roller 56.

The liquid application unit 83B of the seventh preferred embodiment shown in FIG. 15 is constructed of a sheet-like member 88 impregnated with

liquid and held in pressured contact with the press roller 56 via a biasing roller 87, and a supply roller 89a and a winding roller 89b for moving the sheet-like member 88.

With such a seventh preferred embodiment, the sheet-like member 88 impregnated with liquid applies liquid onto the press roller 56 at adjustable abutting contact points to allow the abutting contact point of the press roller 56 to be gradually varied for thereby enabling application of liquid to the press roller 56 in an equally distributed fashion. Also, it is preferred that the sheet-like member 88 is moved at an extremely low speed relative to a peripheral speed of the press roller 56 to enhance an adequate contact between the sheet-like member 88 and the press roller 56. Further, the presence of the adjustable contact point between the sheet-like member 88 and the press roller 56 precludes an inadequate contact between the sheet-like member 88 and the press roller 56 owing to wear of the sheet-like member 88.

The liquid application unit 83C of the eighth preferred embodiment shown in FIG. 16 is constructed of a biasing roller 90 held in pressured contact with the press roller 56 and composed of a biasing member which is able to be impregnated with liquid for retention, and a liquid supply unit 91 which applies liquid in drop phase to the outer periphery of the press roller 56 at a rotational upstream side of the biasing roller 90.

With such an eighth preferred embodiment, liquid supplied to the press roller 56 from the liquid supply unit 91 is equally leveled over the outer periphery 56a of the press roller 56 by means of the biasing roller 90 to uniformly apply liquid over the press roller 56. In addition, since it is possible to adjust the amount of liquid to be applied to the press roller 56 by the liquid supply unit 91, the press roller 56 is allowed to be applied with liquid with an optimum amount to preclude ink transfer in dependence on printing conditions. That is, since the amount of liquid, to be applied to the press roller, optimum for precluding ink transfer is varied according to the printing conditions such as print patterns, qualities of the print sheets and circumstances, it is possible for the press roller 56 to be applied with liquid in an amount optimum for precluding ink transfer in accordance with the printing conditions.

Further, although the biasing roller 90 may be fixedly located, the biasing roller 90 may be arranged to be freely rotated to follow the press roller 56, with a resultant advantage enabling liquid to be applied to the press roller 56 with little rotational load to be exerted thereto. Also, arranging the biasing roller 90 to be freely rotational allows rotational load, to be exerted to the press roller 56, to be substantially completely eliminated.

The liquid application unit 83D of the ninth preferred embodiment shown in FIG. 17 is constructed of a sheet-like member 93 impregnated with liquid and held in pressured contact with the press roller 56 via a biasing roller 92, a supply roller 94a and a winding roller 94b for moving the sheet-like member 93, and a liquid supply unit 95 which applies liquid in drop phase to the outer periphery of the press roller 56 at a rotational upstream side of the biasing roller 92.

With such a ninth preferred embodiment, liquid supplied to the press roller 56 from the liquid supply unit 95 is equally leveled over the outer circumferential periphery 56a of the press roller 56 by means of the sheet-like member 93 to uniformly apply liquid over the outer circumferential periphery 56a of the press roller 56. In addition, since it is possible for the abutting contact point of the sheet-like member 93 relative to the press roller 56 to be varied, gradually adjusting the abutting contact point of the sheet-like member 93 relative to the press roller 56 allows liquid to be uniformly applied to the press roller 56. Also, since the amount of liquid, to be applied to the press roller 56, can be adjusted, it is possible for the press roller 56 to be applied with liquid in an amount optimum for precluding ink transfer in accordance with the printing conditions like in the aforementioned eighth preferred embodiment.

Also, it is preferred that the sheet-like member 93 is moved at an extremely low speed relative to a peripheral speed of the press roller 56 to enhance an adequate contact between the sheet-like member 93 and the press roller 56. Further, the presence of the adjustable contact point between the sheet-like member 93 and the press roller 56 precludes an inadequate contact between the sheet-like member 93 and the press roller 56 owing to wear of the sheet-like member 93.

Liquid used in the aforementioned sixth to ninth preferred embodiments may preferably have the viscosity in the range below 500 millipascal·second and more preferably below 100 millipascal·second. Liquid is composed of, for example, silicone oil.

5 Although the aforementioned respective preferred embodiments have been described with reference to the press roller 56, which serves as the downstream rotary press member of the stencil printing machine which enables the double-phase printing operation and which has the outer circumferential periphery 56a formed with the micro-convexities and
10 concavities, the outer circumferential periphery of the press roller 46, which serves as the upstream rotary press member of the stencil printing machine of the double-phase printing type may be formed with the micro-convexities and concavities, or the outer circumferential periphery of the rotary press member of the stencil printing machine of the single-phase printing type may be
15 formed with the micro-convexities and concavities. That is, although there is an issue wherein there is a chance in that ink is transferred to the rotary press member in a case where the print sheet is not fed to the position between the printing drum and the rotary press member owing to a jamming effect and the press roller 56 is brought into directly pressurized contact with the stencil
20 sheet, in a case where the print sheet, which is smaller in lateral size than the stencil sheet, is fed and the rotary press member is caused to be partly urged into directly pressured contact with the stencil sheet and in a case where the single-phase printing operation is carried out on one surface of the print sheet and subsequently printing operation is carried out on another surface of the
25 print sheet with printing ink in a non-fixed state, causing transferred ink to be further transferred to the print sheet with a resultant contamination thereon, the presence of the micro-convexities and concavities formed over the press roller is highly effective as a contamination measure for the rotary press member and the print sheet.

30 In the aforementioned preferred embodiments, further, although the liquid application unit is constructed of the liquid application roller 70, the liquid application unit may be composed of an expedient which allows liquid to be applied to the outer circumferential periphery of the press roller 56. Also,

although liquid is composed of silicone oil, liquid may be composed of liquid which provides no color formation due to contact between the print sheet 45 and the press roller 56 and which is not mixed with ink, or may be composed of water.

5 In accordance with the various preferred embodiments discussed above, although the rotary press member has been described as being composed of the press rollers 46, 56 with their diameters sufficiently smaller than those of the printing drums 40, 50, the rotary press member may be composed of a member which exerts a printing pressure between the printing drums 40, 50 or
10 may be composed of a press drum with the same diameter as that of the printing drums 40, 50.

As previously described above, in accordance with the stencil printing machine according to the invention, as defined in claim 1, wherein ink is transferred to print medium during the transfer stage in pressured contact thereof to perform the printing operation, the presence of the
15 micro-convexities and concavities formed over the outer circumferential periphery of the rotary press member allows the outer circumferential periphery of the rotary press member to be merely formed with the micro-convexities and concavities such that even when the rotary press member is directly urged toward the stencil sheet, there is a few contact area
20 between the rotary press member and ink or there is a few contact area between the outer circumferential periphery of the rotary press member and the non-fixed ink side of the printing medium. Accordingly, when the rotary press member is separated from the stencil sheet or when the rotary press member is separated from the printing medium, since the aforementioned ink or the non-fixed ink are not appreciably adhered to the rotary press member, it is possible for the printing medium to be prevented from being contaminated in a simplified structure with little decrease in the print density of printing medium.

25 In accordance with the invention as defined in claim 2, the presence of the convexities and concavities with the depth of the value above 0.035 mm formed at the outer circumferential periphery of the rotary press member allows the outer circumferential periphery of the rotary press member to have
30

an increased difference in level in the convexities and the concavities of the outer circumferential periphery of the rotary press member when the rotary press member presses the printing drum via print medium. Thus, the concavities can not be nearly brought into contact with non-fixed ink of print medium for adequately precluding the transfer of non-fixed ink to the rotary press member, ensuring the visible contamination of print medium in a more reliable manner.

In accordance with the invention as defined in claim 3, the presence of the convexities and concavities with the depth of the value above 0.044 mm formed at the outer circumferential periphery of the rotary press member allows the outer circumferential periphery of the rotary press member to have an increased difference in level in the convexities and the concavities of the outer circumferential periphery of the rotary press member when the rotary press member presses the printing drum via print medium. This allows the concavities to remain in little or no contact with non-fixed ink and the transfer of non-fixed ink to the rotary press member can be adequately minimized, ensuring the visible contamination of print medium in a more reliable manner.

In accordance with the invention as defined in claim 4, the presence of the convexities and concavities, with the distance between the apexes in the range below 0.64 mm, formed at the outer circumferential periphery of the rotary press member allows the distance between the convexities and the concavities formed at the outer circumferential periphery of the rotary press member to have a narrow value when the rotary press member presses the printing drum via print medium to interrupt a visible convexity and concavity pattern from appearing on the print image, with a resultant image in a high quality.

In accordance with the invention as defined in claim 5, the presence of the convexities and the concavities, composed of the point-like convexities and concavities, of the outer circumferential periphery of the rotary press member allows the outer circumferential periphery of the rotary press member to be substantially equally formed with the convexities and the concavities in any direction, thereby precluding ink transfer in a substantially equal fashion in whole directions.

5 In accordance with the invention as defined in claim 6, the presence of the convexities and the concavities, composed of the line-shaped convexities and concavities orientated in the same direction as that which print medium is transferred, of the outer circumferential periphery of the rotary press member allows the outer circumferential periphery of the rotary press member to be regularly formed with definite convexities and the concavities in a direction perpendicular to the axial direction of the outer circumferential periphery of the rotary press member, thereby reliably preventing ink transfer in the direction perpendicular to the orientated direction of the line-shape.

10 In accordance with the invention as defined in claim 7, the presence of the convexities and the concavities including the point-like convexities and concavities, composed of the screen mesh, of the outer circumferential periphery of the rotary press member allows the screen mesh per se to be individually prepared which is located over the outer circumferential periphery of the rotary press member by covering the same with the mesh screen or by adhering the screen mesh to the same to form the micro-convexities and concavities, providing an ease of preparation of the point-like convexities and concavities.

15 In accordance with the invention as defined in claim 8, the presence of the convexities and the concavities including the point-like convexities and concavities, composed of the large number of spherical bodies, of the outer circumferential periphery of the rotary press member allows the large number of spherical bodies per se to be individually prepared which are located over the outer circumferential periphery of the rotary press member by adhesion to form the micro-convexities and the micro-concavities, providing an ease of preparation of the point-like convexities and concavities.

20 In accordance with the invention as defined in claim 9, the presence of the liquid application unit, which applies liquid over the outer circumferential periphery of the rotary press member, prevents a non-fixed ink portion from being split while allowing a liquid portion to be split, when the pressurized rotational member and print medium are separated from one another, for thereby precluding the rotary press member from being adhered with non-fixed ink, substantially completely avoiding print medium from being

contaminated.

5 In accordance with the invention as defined in claim 10, the presence of liquid with the viscosity of a value below 1000 millipascal·second allows the liquid portion to be reliably split when the rotary press member and print medium are separated from one another to interrupt non-fixed ink from being adhered to the rotary press member for thereby completely preventing the contamination of print medium.

10 In accordance with the invention as defined in claim 11, the presence of liquid with the viscosity of a value below 500 millipascal·second allows the liquid portion to be reliably split when the rotary press member and print medium are separated from one another to interrupt non-fixed ink from being adhered to the rotary press member for thereby completely preventing the contamination of print medium.

15 In accordance with the invention as defined in claim 12, the presence of liquid composed of silicone oil allows the advantages of the invention of claims 10 to 12 to be obtained.

20 In accordance with the invention as defined in claim 13, the liquid application roller rotates with the rotary press member to apply liquid over the rotary press member with little rotational load to be exerted thereto.

25 In accordance with the invention as defined in claim 14, since the sheet-like member, impregnated with liquid, can be brought into pressured contact with the rotary press member at adjustable contact positions, gradually varying the contact positions at which the rotary press member is held in contact enables liquid to be applied to the rotary press member in a uniform fashion.

30 In accordance with the invention as defined in claim 15, the presence of the liquid supply unit, which can adjust the amount of liquid to be applied to the rotary press member, allows the amount of liquid to be adjusted to a value optimum for avoiding ink transfer according to the printing conditions, etc.

In accordance with the invention as defined in claim 16, since liquid, which is supplied to the rotary press member from the liquid supply unit, is completely applied to the outer circumferential periphery of the rotary press member with the sheet-like member, it is possible for the point of the

sheet-like member, with which the rotary press member is held in abutting contact, to be varied while enabling adjustment of the amount of liquid to be applied to the rotary press member by means of the liquid supply unit. Accordingly, varying the abutting contact point of the sheet-like member relative to the rotary press member in a gradual manner allows liquid to be applied to the rotary press member in a uniform manner while enabling application of liquid at an adjusted amount, optimum for avoiding ink transfer, according to the print conditions, etc.

In accordance with the stencil printing machine according to the invention, as defined in claim 17, wherein the stencil printing machine has two sets of printing sections at the upstream side and the downstream side to perform the double-phase printing operation, the presence of the micro-convexities and the micro-concavities formed over the outer circumferential periphery of at least the downstream rotary press member allows the outer circumferential periphery of the downstream rotary press member to be merely formed with the micro-convexities and concavities such that there is little contact area between the outer circumferential periphery of the downstream rotary press member and the non-fixed ink side surface of the printing medium. Accordingly, when the rotary press member is separated from printing medium, since the rotary press member is not appreciably adhered with non-fixed ink, it is possible for the printing medium to be prevented from being contaminated in a simplified structure with little decrease in the print density of printing medium.

In accordance with the invention as defined in claim 18, the presence of the convexities and concavities with the depth of the value above 0.035 mm formed at the outer circumferential periphery of the rotary press member allows the outer circumferential periphery of the rotary press member to have an increased difference in level in the convexities and the concavities of the outer circumferential periphery of the rotary press member when the rotary press member presses the printing drum via print medium. Thus, the concavities can not be nearly brought into contact with non-fixed ink of print medium for adequately precluding the transfer of non-fixed ink to the rotary press member, ensuring the visible contamination of print medium in a more

reliable manner.

In accordance with the invention as defined in claim 19, the presence of the convexities and concavities with the depth of the value above 0.044 mm formed at the outer circumferential periphery of the rotary press member allows the outer circumferential periphery of the rotary press member to have an increased difference in level in the convexities and the concavities of the outer circumferential periphery of the rotary press member when the rotary press member presses the printing drum via print medium. This allows the concavities to remain in little or no contact with non-fixed ink and the transfer of non-fixed ink to the rotary press member can be adequately minimized, ensuring the visible contamination of print medium in a more reliable manner.

In accordance with the invention as defined in claim 20, the presence of the convexities and concavities, with the distance between the apexes in the range below 0.64 mm, formed at the outer circumferential periphery of the rotary press member allows the distance between the convexities and the concavities formed at the outer circumferential periphery of the rotary press member to have a narrow value when the rotary press member presses the printing drum via print medium to interrupt a visible convexity and concavity pattern from appearing on the print image, with a resultant image in a high quality.

In accordance with the invention as defined in claim 21, the presence of the convexities and the concavities, composed of the point-like convexities and concavities, of the outer circumferential periphery of the rotary press member allows the outer circumferential periphery of the rotary press member to be substantially equally formed with the convexities and the concavities in any direction, thereby precluding ink transfer in a substantially equal fashion in whole directions.

In accordance with the invention as defined in claim 22, the presence of the convexities and the concavities, composed of the line-shaped convexities and concavities orientated in the same direction as that which print medium is transferred, of the outer circumferential periphery of the rotary press member allows the outer circumferential periphery of the rotary press member to be regularly formed with definite convexities and the concavities in a direction

perpendicular to the axial direction of the outer circumferential periphery of the rotary press member, thereby reliably preventing ink transfer in the direction perpendicular to the orientated direction of the line-shape.

5 In accordance with the invention as defined in claim 23, the presence of the liquid application unit, which applies liquid over the outer circumferential periphery of the rotary press member, prevents a non-fixed ink portion from being split while allowing a liquid portion to be split, when the pressurized rotational member and print medium are separated from one another, for
10 thereby precluding the rotary press member from being adhered with non-fixed ink, substantially completely avoiding print medium from being contaminated.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215